

Gasoline Generator

460 cc, 4-stroke 10000 w engine with considerable performance

- 25 Liter full steel fuel tank provides up to 6.5 hours of run time
- Special compact designfor ease of use and better portability
- Circuit breaker outlets for added protection
- Minimum sound and vibration in indoor usage
- 100% copper-wound generator head allows continuous operation without overheating
- Includes one (12V) DC outlets
- Ideal for workshops and light-duty industrial usage

Model	RH-4784	
Generator	Туре	Gasoline Generator
	AC Voltage	220V
	Rated Amperage	32A
	Frequency	50Hz
	Max. Output	7.5KW
	Rated Output	7KW
	Power Factor	1
	DC Output	DC 12V, 8.3A
Engine	Model	FC192F
	Туре	Single Cylinder, 4-Stroke, Forced Air Cooled
	Bore×Stroke	92mm×69mm
	Displacement	460cc
	Max. Output	10KW/3600RPM
	Fuel	Gasoline
	Fuel tank Capacity	25 Lit
	Rated Continuous Operation	6.5 hr
	Lubricating oil	SAE 10W-30
	Lubricating oil Capacity	1.1 Liter
	Starting System	Recoil & E-start
	Ignition system	T.C.I
	Spark Plug: Type	F7TC/F7RTC

POWER TOOLS

RH-4784









POWER TOOLS

Engine	Maximum fuel consumption rate	3.85 Lit/hr
Dimension	Net Dimension L×W×H	686×516×560mm
	Overall Dimension L×W×H	740×575×625mm
	Net Weight	86Kg
	Gross Weight	88Kg
Supplied in	Carton	
Include	2 Plug, 1 Spark Plug Sleeve, 1 Rod, one 12V DC Output Clip, 2 Key, 1 Set Wheels and Handles	